\$ BENETEAU FIRST 14

STANDARD CONFIGURATION & OPTIONS SPECIFICATIONS

Version 1.3_ENG, August 2022, valid for orders under Pricelist 2023B



TECHNICAL DATA

TECHNICAL SPECIFICATIONS

Hull length: 4,30 m / 14'1"

• Beam: 1,70 m / 5'7"

Draft: lifted daggerboard 0,11 m, lowered daggerboard 0,98 m / 4", 3'3"

Hull Weight: 72 kg / 159 lbs

• Sailing weight (MLC*): 110 kg / 243 lbs

Design category: D2
Mainsail: 7,7 m² / 83 ft²
Jib: 2,9 m² / 31 ft

• Gennaker: 13,2 m² / 142 ft

Air draft: 6,10 m / 20 ft

· Naval architect: Samuel Manuard

· Industrial design: Gigodesign

Concept and R&D: Seascape

STANDARD CONFIGURATION

CONSTRUCTION

- Vinyl-ester vacuum infused hull, deck and structure with PVC foam cored sandwich and glass-fibres
- · Hull and deck moulded in single tone off-white gelcoat
- Rolled nonskid on the cockpit floor
- D2 design category following European Directive and CE certification requirements

DAGGERBOARD & STEERING ARRANGEMENT

- Two daggerboard casings (forward casing for full sail set setup, aft casing for mainsail only configuration)
- · One GRP daggerboard in the gelcoat finish
- One GRP rudder blade in the gelcoat finish
- Anodised and powder-coated aluminium rudder box with carbon tiller and Ronstan Battlestick tiller extension

COCKPIT

- Adjustable central foot strap with elastics
- Attachment points on the sides of the hull and on the inside of the cockpit in the stern for the "Removable wheels" option

RIG

- · Two-section aluminium mast with spreaders
- Aluminium boom
- Carbon bowsprit, UV protected
- Mainsail and jib halyard
- 1/19 3 mm / 0,12 inch shrouds with stay adjusters on the side shrouds

MAINSAIL CONTROLS

- · Mainsheet with blocks, a-frame and cleat on the boom
- Aluminium gnav (upside-down vang) system with purchase and cleat on the mast foot
- · Cunningham purchase with a cleat on the mast foot
- Outhaul with cam cleat under the boom

JIB CONTROLS

- · Jib furler and furling line
- · Continous jib halyard in the zip-pocket with jib cunningham
- Self-tacking jib track with adjustable limiters, jib sheet, blocks and cleat on the mast foot

GENNAKER CONTROLS

- Gennaker snuffer
- Continuous single-rope gennaker halyard and retriever line with cleat and blocks
- Bowsprit extension system operated and connected with the gennaker halyard
- · Continuous gennaker sheets with automatic ratchet blocks

SAILS

- North Sails mainsail (Dacron) with small square top, 7,7 m² / 83 ft²
- North Sails jib (Dacron), furling, 2,9 m² / 31 ft²

OPTIONS SPECIFICATIONS

FIRST 14 GENNAKER SET IN CHOSEN COLOUR

- North Sails gennaker with retriever attachment points, Nylon material, 13 m² / 140 sq. ft.
- Retractable carbon bowsprit with running rigging equipment, controlled over the gennaker halyard
- Gennaker halyard and retriever line as continuous single-rope, with cleat and blocks

- Continuous gennaker sheets with automatic ratchet blocks
- Gennaker snuffer
- · Gennaker colour options WHITE, DARK BLUE or BLACK

CUSTOM COLOUR HULL WRAP

Hull wrapping with folio in custom colour

BOAT OVER-BOOM STORAGE COVER

For on-land storage with stepped mast and rigged boom

TRANSPORT COVER

 Top and bottom cover for transport on the roof or trolley, with custom openings for removable wheels

REMOVABLE WHEELS

- Anodized and powder-coated aluminium base with inflatable tyres
- Unique fixation on the hull with screw
- · Possible storage on the stern of the boat while sailing

TROLLEY

Galvanized steel trolley with inflatable tyres for slip-launching and storage in the club

*MLC: Mass of the boat in Light Craft Condition includes the weight of the boat in the standard ready-to-navigate configuration, keel, standard equipment, sails (mainsail & jib) and engine

Beneteau First 14 - Standard Configuration & Options Specifications, Version 1.2, ENG, January 2022

Seascape d.o.o., Podpeč 53, 1352 Preserje, Slovenia.

Specifications and descriptions are provided only for your guidance and are subject to change without prior notice.

www.beneteau.com